

5 Megapixel SWIR Prime Lens C-Mount Fixed-Focal for SWIR Cameras


SP-SWIR3514MC

[SPECIFICATIONS]



Resolution (MFT)		100lp/mm		
Image Format		ø13 > 2/3"		
Focal Length		35±5%mm		
Aperture(F/No)		F1.4 ~ 16		
Mount		C-Mount		
Angle of View (°)		2/3"	1/2"	2/3"
D X H X V (°)	D	-°	-°	-°
	H	14.4°	11.80°	10.50°
	V	10.8°	8.80°	7.90°
Optical Distortion (TV)		<-0.05%		
M.O.D.		0.25m - ∞		
Flange Back Focal Length		17.526mm(in air)		
Back Focal Length		mm(in air)		
Mechanical Back Focal Length		mm(in air)		
Operation	Iris	Manual		
	Focus	Manual		
	Zoom	/		
Working Wavelength		900 – 1700nm		
Filter Size		M40.5 x 0.5P		
Structure		Aluminium Alloy + 8G		
Dimension		ø44.0 × 48.50mm		
Weight		Approx. 178g		
Operating temperature		-30℃~+70℃		

[DIMENSIONS]



Size tolerance (mm)	0-10 $\pm$ 0.05	10-30 $\pm$ 0.10	30-120 $\pm$ 0.20
Angle tolerance	$\pm$ 2°		

All data subject to change without notice

09/15/15 Megapixel ITS Lens Rev A

<http://www.superiorcctv.com> or <http://www.superiorcctv.cn>

Fuzhou Superior® Electronic and Technology Co.,Ltd. - 福州思普锐电子科技有限公司

1 / 1

10/F • Changan Building • No.20 East Yangqiao Rd • Fuzhou • Fujian Province • China • Zip Code 350001 中国 • 福建 • 福州

Tel: +86(591)-8379-6881 • Fax: +86(591)-8379-6882 • Email: info@superiorcctv.com or sales@superiorcctv.com